



# 12 Canadian Price Sheet

## Base Model Intercoms

Model Number	Description	Supply Voltage	Operating Temperature	Shipping Weight	Canadian Price
<b>Wall mount models</b>					
AD-26	Talk/Listen switch, Volume control	12VDC	-31°F to 150°F (-35°C to 65.5°C)	11 lbs (4.98 kg)	\$601.00
AD-56	Talk/Listen switch, Volume control	24VDC	-31°F to 150°F (-35°C to 65.5°C)	11 lbs (4.98 kg)	\$625.00
AD-27	Talk/Listen switch, Volume control	120VAC, 50/60 Hz	-31°F to 150°F (-35°C to 65.5°C)	11 lbs (4.98 kg)	\$625.00
AD-57	Talk/Listen switch, Volume control	240VAC, 50/60 Hz	-31°F to 150°F (-35°C to 65.5°C)	11 lbs (4.98 kg)	\$638.00
<b>Panel mount models</b>					
AD-26P	Talk/Listen switch, Volume control*	12VDC	-31°F to 150°F (-35°C to 65.5°C)	2 lbs (0.90 kg)	\$505.00
AD-56P	Talk/Listen switch, Volume control*	24VDC	-31°F to 150°F (-35°C to 65.5°C)	2 lbs (0.90 kg)	\$519.00
AD-27P	Talk/Listen switch, Volume control*	120VAC, 50/60 Hz	-31°F to 150°F (-35°C to 65.5°C)	2 lbs (0.90 kg)	\$534.00
AD-57P	Talk/Listen switch, Volume control*	240VAC, 50/60 Hz	-31°F to 150°F (-35°C to 65.5°C)	2 lbs (0.90 kg)	\$534.00
*speaker sold separately					
<b>Hazardous Location Wall Mount</b>					
AD-28X-MV	Talk/Listen switch, Volume control, Multi-voltage	24VDC-120VAC	-31°F to 150°F (-35°C to 65.5°C)	11 lbs. (4.98 kg)	\$887.00
<b>Light Duty Wall Mount</b>					
AD-28LD-MV	Talk/Listen switch, Volume control, Multi-voltage	24VDC-120VAC	-31°F to 150°F (-35°C to 65.5°C)	3.56 lbs. (1.62 kg)	\$393.00

## Speakers

Model Mounting	Description	Supply Voltage	Frequency Response	Operating Temperature	Shipping Weight	Canadian Price
<b>Flush mount model</b>						
AD-SF-25	25-Watt Speaker	N/A	800 - 5000 Hz	-31°F to 150°F (-35°C to 65.5°C)	9 lbs. (4.08 kg)	\$267.00
<b>Swivel mount model</b>						
AD-SS-25	25-Watt Speaker	N/A	800 - 5000 Hz	-31°F to 150°F (-35°C to 65.5°C)	9 lbs. (4.08 kg)	\$278.00
<b>Wall mount model</b>						
AD-SO-25	25-Watt Speaker	N/A	800 - 5000 Hz	-31°F to 150°F (-35°C to 65.5°C)	10 lbs. (4.53 kg)	\$252.00
AD-SV-25	25-Watt Speaker, Volume control	N/A	800 - 5000 Hz	-31°F to 150°F (-35°C to 65.5°C)	10 lbs. (4.53 kg)	\$317.00
AD-26SA-25	25-Watt Speaker, Amplifier*	12VDC	800 - 5000 Hz	-31°F to 150°F (-35°C to 65.5°C)	11 lbs. (4.98 kg)	\$371.00
AD-27SA-25	25-Watt Speaker, Amplifier*	120VAC	800 - 5000 Hz	-31°F to 150°F (-35°C to 65.5°C)	11 lbs. (4.98 kg)	\$387.00
AD-57SA-25	25-Watt Speaker, Amplifier*	240VAC	800 - 5000 Hz	-31°F to 150°F (-35°C to 65.5°C)	11 lbs. (4.98 kg)	\$392.00

\* Includes volume control

## Optional Features

Feature ID	Description	Detail Description	Canadian Price
A	Call button	Unit is equipped with a Call Button that generates an attention getting tone.	\$47.00
C	Master unit	Master Unit monitors and controls Slave unit. Defaults to speaker (or Listen) mode.	\$54.00
D	Slave unit	Slave Unit defaults to microphone (or Talk) mode.	\$54.00
- 1	Remote power	120VAC unit is designed to supply power to a 12VDC unit.	\$47.00
- 2	Foot Pedal Ready	Unit is designed for hands-free activation of the Talk/Listen Switch. Foot Pedal sold separately.	\$41.00
- 3	Auxiliary Signal	Call Button activates an attention-getting strobelight. Strobe light sold separately.	\$36.00
- 4	Extreme Conditions	Designed to operate in extremely low temperatures -50° F to +150° F (-45°C to 65°C)	\$47.00
- 6	Zone System Remote	Unit is designed to be the remote unit in a zoned system Remote Activation of the Talk/Listen Switch enables communication to the control unit at any time, even when that zone is not selected. Call the Factory for assistance designing a zoned system.	\$54.00
- 7	Noise-Canceling Microphone Ready	Unit is equipped with a jack for a noise-canceling, Hand-held microphone. Microphone sold separately.	\$54.00
- 8	Pre-Amp Equipped	Unit is equipped with a Pre-Amp to drive a remote speaker. Speaker sold separately.	\$54.00
- M44	Remote Volume Control Equipped	Unit is equipped with a volume control for a remote speaker. Speaker sold separately.	\$35.00

## Auxiliary Strobe Lights

Model	Supply Voltage	Current Draw	Mounting	Lens Color	Shipping Weight	Canadian Price
LP3P-012-048A	12-48VDC	0.44 - 0.10 amp	Pipe	Amber	0.53 lbs (0.24 kg)	\$90.00
LP3P-012-048R	12-48VDC	0.44 - 0.10 amp	Pipe	Red	0.53 lbs (0.24 kg)	\$86.00
LP3S-012-048A	12-48VDC	0.44 - 0.10 amp	Surface	Amber	0.53 lbs (0.24 kg)	\$92.00
LP3S-012-048R	12-48VDC	0.44 - 0.10 amp	Surface	Red	0.53 lbs (0.24 kg)	\$92.00
LP3P-120A	120VAC	0.10 amp	Pipe	Amber	0.53 lbs (0.24 kg)	\$90.00
LP3P-120R	120VAC	0.10 amp	Pipe	Red	0.53 lbs (0.24 kg)	\$90.00
LP3S-120A	120VAC	0.10 amp	Surface	Amber	0.53 lbs (0.24 kg)	\$89.00
LP3S-120R	120VAC	0.10 amp	Surface	Red	0.53 lbs (0.24 kg)	\$89.00
LP3P-240A	240VAC	0.07 amp	Pipe	Amber	0.53 lbs (0.24 kg)	\$97.00
LP3P-240R	240VAC	0.07 amp	Pipe	Red	0.53 lbs (0.24 kg)	\$97.00
LP3S-240A	240VAC	0.07 amp	Surface	Amber	0.53 lbs (0.24 kg)	\$97.00
LP3S-240R	240VAC	0.07 amp	Surface	Red	0.53 lbs (0.24 kg)	\$97.00

## Accessories

Model	Description	Shipping Weight	Canadian Price
ADNCM	Noise Canceling Microphone: hand-held microphone for use with intercoms equipped with the -7 option.	2 lbs (0.90 kg)	\$162.00
ADFP	Foot Pedal: heavy-duty foot pedal for use to activate Talk/Listen function on intercoms equipped with the -2 option.	8 lbs (3.62 kg)	\$271.00