



Hazardous Location Wall Mount Intercom Model AD-28X-MV

Designed for single-channel, two-way indoor and outdoor communication applications, the Hazardous Location Wall-Mount Intercoms are rated for Class I, Division 2, Groups A, B, C, & D; Class II, Division 2, Groups F & G; and Class III. Features include integrated volume control, Talk/Listen switch, corrosion resistant cast aluminum housing with rugged powder coat finish (Type 4X, IP65 enclosure), reliable 25-watt speaker and balanced line output. These heavy-duty units are UL and cUL Listed, CSA Certified and Marine rated and are designed for multi-voltage operation: 24VDC, 120VAC and 240 VAC, 50/60Hz.

- Heavy-duty industrial intercom for indoor or outdoor applications
- Single channel, two-way communications
- Integrated volume control and Talk/Listen switch
- Call Button
- Balanced line output
- 25 watt speaker
- Cast aluminum housing with rugged powder coat finish
- Multi-voltage operation: 24VDC, 120VAC and 240VAC
- UL and cUL Listed, CSA Certified, Marine Rated
- Type 4X, IP65 enclosure
- Field configurable master/slave operating mode
- Remote power capable @24VDC
- Auxiliary signal activation contact



Model	Voltage Current	Operating Current	Stand-by Response	Frequency
AD-28X-MV	24VDC	260mA	62mA	320Hz to 8.0Khz
	120VAC	163mA	70mA	320Hz to 8.0Khz
	240VAC	82mA	35mA	320Hz to 8.0Khz

Product Specifications

Speaker Rating	30 watt	30 watt
Operating temperature	-31°F to 150°F	-50°C to 66°C
Net weight	9.0 lbs	4.08 Kg
Shipping weight	11 lbs	4.99 Kg
Dimensions		
Height	9.90 in	25.15 cm
Width	6.70 in	17.02 cm
Depth	3.88 in	9.86 cm

