



ATKINSON DYNAMICS

**COMMUNICATIONS
FOR INDUSTRY**

Accessories

Noise Cancelling Microphone

- Designed to cancel out 90% of background noise
- Standard 6 foot (1.82m) coiled cord, retracts to only 1 foot (0.03m)
- Comfortable 3 inch (7.62cm) wide by 4 inch (10.16cm) high microphone body with a large side mounted push-to-talk button.
- Intercom requires the (-7) option, noise canceling microphone ready ordering information - ADNCM



Foot Pedal

- For hands free Push To Talk capability
- Heavy-duty cast iron construction
- Complies with OSHA requirements for full shielding
- Finished in a bright safety orange paint
- Oil and water tight construction, NEMA rated 2, 4, and 13
- Large 6 inch (15.24cm) wide by 4.5 inch (11.43cm) high pedal opening for ease of operation
- Requires the (-2) option, Foot Pedal Ready
Ordering information - ADFP



Auxiliary Strobe Light

- ADLP3S – surface mount, ADLP3P – 1/2" pipe mount
- 175,000 peak candela
- 7000 hour lamp life
- Type 4X, IP66 construction
- Available: Red or Amber lens
- Available: 12-48VDC or 120VAC, 50/60Hz
- Activated by a second intercom equipped with the Call Button (A) and Auxiliary Signal (-3)



Ordering information -

Model	Voltage	Current Draw	Mounting	Color
LP3P-012-048A	12-48VDC	0.44 - 0.10 amp	Pipe	Amber
LP3P-012-048R	12-48VDC	0.44 - 0.10 amp	Pipe	Red
LP3S-012-048A	12-48VDC	0.44 - 0.10 amp	Surface	Amber
LP3S-012-048R	12-48VDC	0.44 - 0.10 amp	Surface	Red
LP3P-120A	120VAC	0.10 amp	Pipe	Amber
LP3P-120R	120VAC	0.10 amp	Pipe	Red
LP3S-120A	120VAC	0.10 amp	Surface	Amber
LP3S-120R	120VAC	0.10 amp	Surface	Red
LP3P-240A	240VAC	0.07 amp	Pipe	Amber
LP3P-240R	240VAC	0.07 amp	Pipe	Red
LP3S-240A	240VAC	0.07 amp	Surface	Amber
LP3S-240R	240VAC	0.07 amp	Surface	Red