



## Desk Top Intercom

Compatible with either desktop- or wall-mount configurations, single-channel Desktop Intercoms highlight sleek, professional styling that includes an integrated push-to-talk button in the hand set and a conveniently located volume control on the face of the unit. Models are available in 12 or 24VDC and 120 and 240VAC, 50/60Hz.

- Sleek professional phone design
- Desktop
- Single channel, two way communications
- Integrated call button in the hand set
- Volume control on the base
- Available; 12 or 24VDC and 120 240VAC, 50/60Hz

Model	Voltage	Operating Current	Stand-by Current
AD-26T	12VDC	130mA	24mA
AD-27T	120VAC	42mA	24 mA
AD-56T	24VDC	198mA	31mA
AD-57T	240VAC	21mA	14.5mA



## Optional Features

- Master (C), controls Talk/Listen function of a Slave unit.
- Slave (D), allows hands free operation, default Talk mode
- Auxiliary Signal (-3), remote call button activated contact closure to activate remote strobe for additional attention gathering.
- Zoned System Remote (-6), designed to be a remote unit in a zoned system. Contact factory for zone design assistance.
- Pre-Amp Equipped (-8), pre-amp to power a remote speaker.

Note: Some restrictions apply when combining optional features. Consult factory for details.

## Product Specifications

Operating temp	-22°F to 167°F	-30°C to 75°C
Net weight	4 lbs	1.81 Kg
Shipping weight	5 lbs	2.27 Kg
Dimensions (without handset)		
Height	8.75 in	22.26 cm
Width	7.75 in	19.69 cm
Depth	4.50 in	11.43 cm

