



ATKINSON DYNAMICS
COMMUNICATIONS
FOR INDUSTRY

Speakers

Available for both indoor and outdoor applications, 25-watt Speakers feature a heavy duty cast aluminum housing with powder coat finish, TALK-BACK capability and optional integrated volume control. Speakers are available for flush, wall, and swivel mounting.

- 25 Watt speakers
- Heavy duty cast aluminum housing
- Powder coat paint finish
- Talk back capability
- Available; Flush mount, Wall mount and Swivel mount models
- Optional integrated volume control, select models
- Designed for indoor or outdoor applications
- NEMA Type 4X, IP66, Non-amplified speaker
- NEMA Type 4X, IP56, Amplified speaker

Non-Amplified Speakers

Requires option (-8), Pre-Amp Equipped

Model	Mounting	Impedance	Frequency Response
AD-SF-25	Flush	16 Ohms	400 – 4000Hz
AD-SS-25	Swivel	8 Ohms	400 – 4000HZ
AD-SO-25	Wall	8 Ohms	400 – 4000HZ
AD-SV-25	Wall*	8 Ohms	400 – 4000HZ

*with volume control



Amplified Speakers

Model	Voltage	Operating Current	Stand-by Current	Frequency Response
AD-26SA-25	12VDC	1.47A	100mA	320Hz to 8.0Khz
AD-27SA-25	120VAC	240mA	83mA	320Hz to 8.0Khz
AD-57SA-25	240VAC	127mA	83mA	320Hz to 8.0Khz

Product Specifications

Power Handling	25 watts	25 watts
Operating temp.	-50°F to 150°F	46°C to 66°C

Net weight

AD-SF-25	5.0 lbs	2.27 Kg
AD-SS-25	6.0 lbs	2.72 Kg
AD-SO-25	8.0 lbs	3.63 Kg
AD-SV-25	8.0 lbs	3.63 Kg
AD-26SA-25	10.0 lbs	4.54 Kg
AD-27SA-25	10.0 lbs	4.54 Kg
AD-57SA-25	10.0 lbs	4.54 Kg

Shipping weight

AD-SF-25	6.0 lbs	2.72 Kg
AD-SS-25	6.0 lbs	2.72 Kg
AD-SO-25	9.0 lbs	4.08 Kg
AD-SV-25	9.0 lbs	4.08 Kg
AD-26SA-25	11.0 lbs	4.99 Kg
AD-27SA-25	11.0 lbs	4.99 Kg
AD-57SA-25	11.0 lbs	4.99 Kg

Dimensions

AD-SF-25		
Diameter	7.25 in	18.42 cm
Depth	5.00 in	12.70 cm

AD-SS-25		
Height	8.40 in	21.34 cm
Width	6.25 in	15.88 cm
Depth	5.00 in	12.70 cm

AD-SO-25 / AD-SV-25		
Height	9.90 in	25.15 cm
Width	6.70 in	17.02 cm
Depth	3.88 in	9.86 cm

AD-26SA-25 / AD-27SA-25		
AD-57SA-25		
Height	9.90 in	25.15 cm
Width	6.70 in	17.02 cm
Depth	3.88 in	9.86 cm

